






REV.	ECN.NO.	APPD.
A	/	/



材质


塑胶 : PA6T/LCP-UL94 V-0
 端子 : 黄铜
 接触电镀: 镀金 Gold flash

产品参数

额定电流 : 2A
 耐电压值: ≤550V AC
 工作温度: -40° C to +105° C
 接触电阻: ≤20mΩ
 绝缘电阻: ≥1000MΩ
 最大处理温度: 230° C-265° C

216104-1054-G31058

- 1: 吸塑盘
- 2: 吸塑管
- 5: 袋装
- 7: 管装



PCB. LAYOUT

A	H		PC	PA
2P-40P	1.5	2.0	1.5~3.0	2.0~10.0

TOLERANCE UNLESS OTHERWISE SPECIFIED		FLW 深圳市华联威电子科技有限公司				
.XXX ±0.10 .XX ±0.20 .X ±0.30		HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.;LTD.				
APPROVED		PART NAME:	2.0间距排针 单排 直插20PIN			
CHECKED		PART No:	216104-1054-G31058		C	
DRAWN	weihong	PROJECTION:	UNIT:	SCALE	SHEET	
DATE	2021.9.23		mm	1:1	10F1	