



REV.	ECN.NO.	APPD.
A	/	/

NOTES:
 PART NO. : EST2501-WV-XP
 Current Rating: 3A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: $-25^{\circ}C \sim +120^{\circ}C$
 Contact Resistance: 20m max Ω
 Insulation Resistance: 1000M $m\Omega$
 Withstanding Voltage: 800V
 Material: WAFER: PA66 UL 94V-0
 PIN: BRASS/TIPLATED

Recommended P. C. B Layout (Top Side)

P. C. B Thickness = 1.20mm
 (Tolerance = ± 0.05)

PART NO. (90°)	Dimensions	
	A	B
XH2.5-2A	7.50	2.50
XH2.5-3A	10.00	5.00
XH2.5-4A	12.50	7.50
XH2.5-5A	15.00	10.00
XH2.5-6A	17.50	12.50
XH2.5-7A	20.00	15.00
XH2.5-8A	22.50	17.50
XH2.5-9A	25.00	20.00
XH2.5-10A	27.50	22.50
XH2.5-11A	30.00	25.00
XH2.5-12A	32.50	27.50
XH2.5-13A	35.00	30.00
XH2.5-14A	37.50	32.50
XH2.5-15A	40.00	35.00
XH2.5-16A	42.50	37.50

TOLERANCE UNLESS OTHERWISE SPECIFIED	
.XXX ± 0.10	.X* $\pm 3^{\circ}$
.XX ± 0.20	.XX* $\pm 2^{\circ}$
.X ± 0.30	
APPROVED	
CHECKED	
DRAWN	weihong
DATE	2021.7.23

FLW 深圳市华联威电子科技有限公司
 HUA LIAN WEI TECHNOLOGY ELECTRONICS CO.;LTD.

PART NAME:	针座 间距2.5 立插 不带耳 10P			
PART No:	216104-1015-G32018	C		
PROJECTION:	UNIT:	SCALE:	SHEET:	REV.
	mm	1:1	10F1	A