



ECN.NO.	ECN DESCRIPTION	REV.	DATE	APPD.
/	NEW DWG	A	2014.08.27	LWQ
/	产品改善	B	2022.11.10	魏红

- NOTES:
- MATERIAL:
 - Housing:thermoplastic plastics
 - terminals:Copper Alloy
Gold plated in contact area:
Tin plated in termination
Nickel Plated overall
 - Shell:Steel&Copper Alloy
Nickel/Au Plated overall
 - ELECTRICAL CHARACTERISTICS:
 - Rating Current :0.5 Ampere
 - Rating Voltage :40 V Max
 - Contact Resistance:30 Milli ohms
 - Insulation Resistance:100 Mega ohms Min.
 - MECHANICAL CHARACTERISTICS:
 - Connector Mating force: 4.5kg MAX
 - Connector Unmating force:1.0Kg min
 - Durability:10000Cycles.
 - ENVIRONMENT CHARACTERISTICS:
 - Operating temperature:-20°C to +85°C
 - Storage temperature:-20°C to +65°C

HD22-1215-161681

- 5:铜壳镀镍
- 1:1u" Au
- 8:载带
- 1:黑色
- 6:LCP

TOLERANCE UNLESS OTHERWISE SPECIFIED		FLW 深圳市华联威电子科技有限公司 HUA LIAN WEI TECHNOLOGY ELECTRONICS CO;LTD.			
.XXX ±0.10	.X' ±2'	APPROVED	PART NAME: HDMI 19P/F SMT 无后盖无凸点 L=3.80		
.XX ±0.20	.XX' ±1'	CHECKED	PART No:	HD22-1215-161681	C
.X ±0.30		DRAWN	魏红	PROJECTION:	UNIT: SCALE SHEET REV.
		DATE	2022.11.10	mm 1:1 10F1	B